

CENTRIFUGES



**BOECO HAEMATOCRIT
CENTRIFUGE HC-240**



Haematocrit rotor with lid as
evaluation disc included.

capacity	75 µl
Capillaries	1,5 x 75 mm
 Rotor and Lid as evaluation disc incl.	
Cat.-No.	—
capillaries per rotor	24
RCF	16,060
radius in mm	85
run-up in sec	9
run-down in sec ²⁾	16

BOECO HAEMATOCRIT CENTRIFUGE HC-240

High-speed bench-top centrifuge for haematocrit determinations with brushless frequency drive. At 16.060 g sedimentation is completed in just a little over 6 minutes.

The HC-240 centrifuge includes a segmented haematocrit rotor for 24 capillaries. With the segmented haematocrit rotor every capillary has its own chamber. If a capillary breaks, the fragments stay in this chamber or segment without affecting other capillaries.

The lid of the rotor is evaluation disc and cover in one.
The haematocrit value can be read off the lid/evaluation disc right after centrifugation.

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » The centrifuge's speed and running time can be variably adjusted for different applications
- » Speed display in RPM or RCF
 - RPM input from 200 to 10.000 in steps of 10, starting from 10.000 to the maximum speed in steps of 100
 - RCF input from 200 to 10.000 in steps of 1, starting from 10.000 to the maximum speed in steps of 10
- » Time t/min: 1 - 99 min. in steps of 1 min.,
Time t/sec: 1 - 59 sec. in steps of 1 sec.,
Continuous operation
- » Brake stage, selectable between fast and slow
- » Pulse key: For short centrifugation operations
- » Open lid key

Safety

- » Lid locking and holding device
- » Emergency lid lock release
- » Lid closure of metal
- » Imbalance switch-off
- » Flexible motor bearings
- » Deep metal rotor chamber (die-cast-aluminium) to securely accomodate the rotor

Design

- » Smooth plastic housing, easy to clean
- » Metal lid
- » Deep metal rotor chamber

Technical details

Max. RPM (speed) / RCF:	13,000 rpm / 16,060 RCF
Noise level:	≤ 57 dB(A)
Dimensions in mm (HxWxD):	228 x 262 x 352
Net weight:	10 kg
Emission / Immunity :	EN / IEC 61326-1, class B / FCC class B

The HC-240 conforms to safety regulations such as IEC 61010, or the EC mark and all relevant EU standards and DIN norms and has been manufactured under ISO 9001:2015

Code	Description
BOE 01801-13	BOECO centrifuge HC-240, 208-240 V, 50/60 Hz, with haematocrit rotor and lid as evaluation disc
BOE 01801-12	BOECO centrifuge HC-240, 100-127 V, 50/60 Hz, with haematocrit rotor and lid as evaluation disc

BOECO HAEMATOCRIT CENTRIFUGE HI-24

Hematocrit Centrifuge is used for determination of volume fractions of erythrocytes (Red blood cells) in blood and also for separation of micro blood and solutions.

Product Features

- » Brushless DC motor for maintenance free long life
- » Precise RPM setting from 500 to 12000 with least count of 100 RPM
- » Lid lock safety: Lid releases automatically after run completion
- » Timer setting upto 12 minutes
- » RPM & RCF toggles alternatively on the display during operation
- » Large LCD display for easy setting and reading multiple parameters
- » Small footprint saves valuable bench space

Standard Accessories

- » Power Adaptor: Input Voltage: 100-240 V, 50/60 Hz
Output Voltage: 24 V, 6 A
- » 24 slot Capillary rotor (Pre-installed)
- » Blood reader
- » T - Allen wrench
- » Product user manual and Warranty card

Technical details

Rotor Capacity:	24 x 45 / 75 mm length capillary tubes
Max RPM (speed) / RCF:	12,000 rpm / 14118 g
Motor Type:	Brushless DC
Display:	LED Display
Speed Setting:	500 - 12000 RPM in steps of 100 RPM
Timer Setting:	Upon 12 mins
Preset Feature:	2 preset mode (P1 & P2)
Noise level:	≤ 50 dB(A)
Dimensions in mm (HxWxD):	228 x 262 x 352
Weight of Equipment:	4,3 kg (with Rotor)
Dimension (W x D x H)	330 x 265 x 161 mm

Code	Description
BOE 8077000	BOECO haematocrit centrifuge HI-24 with 24V, 6A power supply and EU plug
BOE8077100	BOECO haematocrit centrifuge HI-24 with 24V, 6A power supply and US plug



BOECO CENTRIFUGE HI-24



BOECO CENTRIFUGE SC-8

BOECO CENTRIFUGE SC-8

Practical and handy the SC-8 is the ideal centrifuge for small sample volumens. It is supplied with a 8-place angle steel rotor, which accomodates various tube systems as well as 15 ml glass tubes without adapters. The centrifuge is microprocessor controlled.

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » The centrifuge's speed and running time can be variably adjusted for different applications:
- » Speed display in RPM or RCF
 - RPM input from 200 to the maximum speed in steps of 10
 - RCF input from 200 to the maximum speed in steps of 1
- » Time t/min: 1 - 99 min. in steps of 1 min.,
Time t/sec: 1 - 59 sec. in steps of 1 sec.,
Continuous operation
- » Brake stage, selectable between fast and slow
- » Pulse key: For short centrifugation operations
- » Open lid key

Safety

- » Lid locking and holding device
- » Emergency lid lock release
- » Lid closure of metal
- » Imbalance switch-off
- » Flexible motor bearings
- » Deep metal rotor chamber (die-cast-aluminium) to securely accomodate the rotor

Design

- » Smooth plastic housing, easy to clean
- » Metal lid
- » Deep metal rotor chamber

The SC-8 conforms to safety regulations such as IEC 61010, or the EC mark and all relevant EU standards and DIN norms and has been manufactured under ISO 9001:2015

Technical details

Max RPM (speed) / RCF:	6,000 rpm / 3,461 RCF
Noise level:	≤ 50 dB(A)
Dimensions in mm (HxWxD):	228 x 262 x 352
Net weight:	8,9 kg
Emission / Immunity:	EN / IEC 61326-1, class B / FCC class B

Code

Description

BOE 01800-13	BOECO centrifuge SC-8, 208-240 V, 50/60 Hz, complete with 8-place angle rotor
BOE 01800-12	BOECO centrifuge SC-8, 100-127 V, 50/60 Hz, complete with 8-place angle rotor

capacity in ml	4	5	7	15	15	blood collection / urine tubes			
dimensions Ø x L mm	10 x 88	12/13 x 75	13 x 100	17 x 100	17 x 120	max 17 x 100			
 n=6,000 min ⁻¹ Rotor included									
									
Cat.-No.	06305	01054-A	01058	-	-	-			
tubes per rotor	8	8	8	8	4	8			
RCF	2,817	2,697	3,461	3,461	3,461	3,461			
radius in mm	70	67	86	86	86	99			
run-up in sec	17								
run-down in sec ²⁾	37								

BOECO CENTRIFUGE SC-6

The BOECO SC-6 is a small centrifuge with a swing-out rotor especially designed for use in clinical laboratories and medical practices. It accepts common blood or urine tubes up to a volume of 15 ml and accelerates them to a maximum speed of 4,000 rpm⁻¹

The BOECO SC-6 delivers optimal separation results and a horizontal layer of the separating gel that is identical to that achieved with a large centrifuge. Samples are therefore optimally prepared for analysis.

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » The centrifuge's speed and running time can be variably adjusted for different applications.
- » Speed display in RPM x 100, input in steps of 100
- » Time t/min: 1 - 99 min, continuous operation
- » Pulse key: For short centrifugation operations
- » Open lid key

Safety

- » Lid locking and holding device
- » Centrifuge chamber of stainless steel
- » Emergency lid lock release
- » Lid closure of metal
- » Imbalance switch-off
- » Flexible motor bearings

Design

- » Smooth plastic housing, easy to clean
- » Metal lid
- » Stainless steel centrifugation chamber, deep-drawn and seamless

The SC-6 conforms to safety regulations such as IEC 61010, or the EC mark and all relevant EU standards and DIN norms and has been manufactured under ISO 9001:2015

Technical details


Max RPM (speed) / RCF: 4,000 rpm / 2,254 RCF
Noise level: ≤ 50 dB(A)
Dimensions in mm (HxWxD): 239 x 326 x 389
Net weight: 13,5 kg
Emission / Immunity: EN / IEC 61326-1, class B / FCC class B

Code	Description
BOE 02300-13	BOECO centrifuge SC-6, 200-240 V, 50/60 Hz, complete with 6-place swing-out rotor and carriers 02331 and 02333 (6 of each)



BOECO CENTRIFUGE SC-6



capacity in ml	4	5	6	1,6-7	4-7	8,5-10	15	blood collection / urine tubes
dimensions Ø x L mm	10 x 88	12x75	12x82	13/16x75	13x100	16x100	17x100	max 17 x 100
 n=4,000 min ⁻¹ Rotor and carriers included								
								
Cat.-No.	02331	02333	02333	02333	02331	02331	02331	02331
tubes per rotor	6	6	6	6	6	6	6	6
RCF	2,254	1,807	1,807	1,807	2,254	2,254	2,254	2,254
radius in mm	126	101	101	101	126	126	126	126
run-up in sec	10							
run-down in sec ²⁾	22							



BOECO CENTRIFUGE S-6

BOECO CENTRIFUGE S-6

BOECO centrifuge S-6 is widely used in physical and chemistry analysis, biochemistry, cellular and molecular biology, clinical Labs and blood donation centers

BOECO centrifuge S-6 with fixed Angle Rotor for 6 x 15 ml centrifuge tubes (17 x 100 /120 mm), 3 adapters sets, black adapters Ø 13 x 78 mm for 10 ml / 7 ml / 5 ml blood collection tubes, white adapters Ø 13 x 63 mm for 4 ml / 3 ml / 2 ml blood collection tubes, green adapters Ø 11 x 78 mm for 2,0 / 1,5 ml microtubes, Power Supply AC 100-240 V, 50-60 Hz, Manual

- » Maintenance-free brushless motor
- » LCD Display of time and speed
- » Adjustable speed from 300 rpm to 5000 rpm
- » Time, from 15 s to 99 min
- » Lid automatically opens at the end of the run to prevent sample warming and to reduce handling time
- » Two program button P1/P2 for easy access to routine programs
- » Button rpm/rcf for easy switching between RPM and RCF display
- » Automatic rotor imbalance detection

Technical details

Max RCF:	2500xg
Power supply:	External, AC 100 - 240 V / 50/60 Hz
Rotor Capacity:	6 x 15 ml (with 3 adapter sets 10/7/5ml - 4/3/2ml -1,5/2,0ml)
Speed:	From 300 rpm to 5000 rpm
Time:	15 s – 99 min. / continuous operation
Motor:	Brushless motor
Housing:	ABS, Lid: PC
Dimension:	212 x 270 x 158 mm
Weight:	4,5 kg

Code	Description
BOE 8076000	BOECO centrifuge S-6, 100-240 V, 50/60 Hz, 5000 rpm with angle rotor for 6 x 15 ml tubes and 3 adapter sets

BOECO CENTRIFUGE C-28A

The non-refrigerated microprocessor-controlled C-28A is the ideal bench-top centrifuge for performing daily routine tasks in doctors' laboratories and small hospitals. But because of the wide range of accessories the C-28A can also be used for sample preparation in research and industrial laboratories.

The centrifuge has a brushless frequency drive (no carbon brushes). A special locking device allows effortless opening and closing of the lid with just one hand.

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » Entry of the running parameters via foil keypad
- » Speed display in RPM x 100, input in steps of 100
- » Time t/min: 1 - 99 min, continuous operation
- » Impulse key: For short centrifugation operations

Safety

- » Housing and lid of metal finished in a scratch and impact resistant coating
- » Centrifuge chamber of stainless steel
- » Lid locking and holding device
- » See-through glass in the lid
- » Emergency lid lock release
- » Imbalance switch-off
- » Easily exchangeable rotors
- » Automatic rotor recognition

The C-28A conforms to safety regulations such as IEC 61010 or the EC mark and all relevant EU standards and DIN norms and has been manufactured under ISO 9001:2015

Technical details

Max. RPM (speed) / RCF:	6,000 rpm / 4,226 RCF
Noise level:	< 58 dB(A) (dependent on rotor)
Dimensions in mm: (HxWxD)	257 x 366 x 430
Net weight:	approx. 23 kg
Emission / Immunity:	EN / IEC 61326-1 class B, FCC class B

Code	Description
BOE 01206-13	BOECO centrifuge C-28A, 208-240 V, 50/60 Hz, without rotor
BOE 01206-12	BOECO centrifuge C-28A, 100-127 V, 50/60 Hz, without rotor

capacity in ml	5	4-7	15	15	50	12	50	50
dimensions Ø x L mm	12 x 75	13 x 100	17 x 100	17 x 120	29 x 115	17 x 100	29 x 115	29 x 107
 n=4,000 min ⁻¹ Cat.-No. 01418								
	+ 01054A	+ 00716	+ 00716	+ E2109	+ E2110	+ 00716		
								
Cat.-No.	01467	01467	01467	01467	01468	01467	01468	01468
tubes per rotor	32	32	32	32	8	32	8	8
RCF	2,182	2,612	2,540	2,594	2,486	2,540	2,486	2,486
radius in mm	122	146	142	145	139	142	139	139
run-up in sec	36							
run-down in sec. ²⁾	43							




BOECO CENTRIFUGE C-28A



ROTOR 01418 WITH 01467

Swing-out rotor 01624, 4-place,
illustrated with
carriers 01369
n= 4,000 min⁻¹,
max RCF 2,665,
max. cap. 4 x 100 ml.



90°




Swing-out rotor, 4-place,
01624 illustrated with
carriers 01481 and lids
01492 with bio-
containment

capacity in ml	5	4-7	9	9	15	15	1,6 - 7	20	25	45	50
dimensions Ø x L mm	12/13x75	13x100	14x100	14x100	17x100	17x100	12/13x75 16x75	21x100	24x100	31x100	34x100
 n=4,000 min ⁻¹ rotor Cat.-No. 01624											
											
Cat.-No.	01372	01739	01370	01741	01369	01742	01742	01346	01745	01345	01746
tubes per rotor	68	28	20	40	16	28	28	8	8	4	4
RCF	2,164	2,451	2,308	2,415	2,308	2,415	2,325	2,361	2,451	2,361	2,451
radius in mm	121	137	129	135	129	137	130	132	137	132	137
run-up in sec	22										
run-down in sec. ²⁾	25										

Please take care
not to exceed
the tubes' max.
permissible RCF!

2) braked
run-down

capacity in ml	1	3	5/6/7	4-10	9/15	25	30	50	50	85	100	15	50	1,6 - 7	4 - 10
dimensions Ø x L mm	6x45 rhesus	10 x 60	12 x 75-100	16x75/100	14/17 x 100	24 x 100	26 x 95	29 x 107	34 x 100	38 x 106	44 x 100	17 x 120	29 x 115	13x75/100	16x75/100
 lid with bio- containment 01492 Carrier Cat.-No. 01481															
															
Cat.-No.	01339	01343	01383	01348	01329	01330	04417	04416	01331	01396	00761	01347	01384	01383	01348
tubes per rotor	108	36	20	16	16	4	4	4	4	4	4	4	4	20	16
RCF	2,594	2,630	2,558	2,522	2,540	2,433	2,451	2,630	2,415	2,612	2,558	2,665	2,665	2,558	2,522
radius in mm	145	147	143	141	142	136	137	147	135	146	143	149	149	143	141
run-up in sec	22														
run-down in sec. ²⁾	25														



90°

Swing-out rotor, 4-place 01324,
illustrated with carrier 01398 and
adapter 01483A
n= 4,000 min⁻¹, max RCF 2,522



Swing-out rotor, 4-place 01324,
illustrated with carrier 01490 and
lids 01492
n= 4,000 min⁻¹, max RCF 2,630
for max. 4 x 100 ml

capacity ml	5-7	9	15	2,6-3,4	4-5,5	9-10	10	4-7	15	50	12	50
dimensions Ø x L mm	12x75/82/100	14x100	17x100	13x65	15x75	16x92	15x102	16 x 75	17x120	29x115	17x100	29x115
 n=4,000 min ⁻¹ rotor Cat.-No. 01324 Carrier Cat.-No. 01398												
												
Cat.-No.	01486	01482A	01486	01482A	01482A	01482A	01482A	01482A	01483A	01484	01482A	01484
tubes per rotor	20	16	20	16	16	16	16	16	16	4	16	4
RCF	2,486	2,522	2,486	2,272	2,522	2,397	2,612	2,397	2,612	2,576	2,522	2,576
radius in mm	139	141	139	127	141	134	146	134	146	144	141	144
run-up in sec	27											
run-down in sec. ²⁾	30											

capacity ml	1.5/2.0	1	3/4	5	6/7	9/15	25	50	100	10	30	50	85	15		50	12	25	30	50
dimensions Ø x L mm	11 x 38	6 x 45 Rhesus	10x60/88	12x75	12x82/100	14/17x100	24 x 100	34 x 100	44 x 100	16x80/100	26x95	29x107	38x106	17x120		29x115	17x100	25 x 90	25x110	29x115
lid No. 01492 biocontainment ²⁾																				
Carrier Cat-No. 01490																				
Cat.-No.	01351	01339	01343	01383	01383	01329	01330	01331	00761	01348	04417	04416	01396	01356	01347	01384	06311	01363	01365	06318
tubes per rotor	20	108	36	20	20	16	4	4	4	16	4	4	4	12	4					
RCF	2,415	2,558	2,594	2,522	2,522	2,504	2,397	2,379	2,522	2,486	2,415	2,594	2,576	2,630			2,308		2,630	
radius in mm	135	143	145	141	141	140	134	133	141	139	135	145	144	147			129		147	
run-up in sec	27																			
run-down in sec. ²⁾	30																			

90°



Swing-out rotor, 8-place,
for 8 x 15 ml,
 $n = 4,000 \text{ min}^{-1}$, RCF 2,415
Stainless steel, with
suspensions No. 01644, PA, fib-
reglass reinforced.

capacity in ml	5	4-7	10	15
dimensions Ø x L mm	12/13x75	17 x 70	13 x 100	17 x 100
 n=4,000 min ⁻¹ Cat.-No. 01611				
				
Cat.-No.	01131-A	01132-A	01643	01644
tubes per rotor	8	8	8	8
RCF	1,914		2,415	
radius in mm	107		135	
run-up in sec	22			
run-down in sec. ²⁾	25			



Swing-out rotor, 12-place,
for 12 x 15 ml
 $n = 4,000 \text{ min}^{-1}$, RCF 2,683,
Stainless steel, with suspensions
No. 01621, PA, fiberglass rein-
forced.

capacity in ml	5	4-7	15
dimensions Ø x L mm	12/13 x 75	15/16 x 75	17 x 100
			
$n = 4,000 \text{ min}^{-1}$ Cat.-No. 01628			
Cat.-No.	01127-A	01122	01621
tubes per rotor	12	12	12
RCF	2,236	2,254	2,683
radius in mm	125	126	150
run-up in sec.	22		
run-down in sec. ²⁾	25		

45°



Swing-out rotor, 8-place,
for 8 x 50/15 ml Falcon tubes
 $n = 4,000 \text{ min}^{-1}$, RCF 2,469
stainless steel, with
suspensions, aluminium.

capacity in ml	15	50
dimensions Ø x L mm	17 x 120	29 x 115
		
$n = 4,000 \text{ min}^{-1}$ Cat.-No. 01617		
Cat.-No.	01462A	—
tubes per rotor	8	
RCF	2,469	
radius in mm	138	
run-up in sec.	22	
run-down in sec. ²⁾	25	

90°



Swing-out rotor, 6-place,
for 6 x 50/15 ml Falcon tubes
 $n = 4,000 \text{ min}^{-1}$, RCF 2,701,
Stainless steel, with suspensions,
PA, fiberglass reinforced.

capacity in ml	15	50
dimensions Ø x L mm	17 x 120	29 x 115
		
$n = 4,000 \text{ min}^{-1}$ Cat.-No. 01619		
Cat.-No.	01462-A	—
tubes per rotor	6	
RCF	2,701	
radius in mm	151	
run-up in sec.	22	
run-down in sec. ²⁾	25	

35°



Angle rotor, 6-place,
Cat. No. 01620»
 $n = 6,000 \text{ min}^{-1}$,
max. RCF 4,226
illustrated with adapter set 01646

capacity in ml	10	15	30	50	50	85	15	50
dimensions Ø x L mm	16 x 80	17 x 100	26 x 95	29 x 107	34 x 100	38 x 106	17 x 120	29 x 115
 n=6,000 min ⁻¹ Cat.-No. 01620A								
								
Cat.-No.	01448	01451	01447	01446	01463	—	01466	01646
tubes per rotor	12	6	6	6	6	6	6	6
RCF	3,904	3,904	3,824	4,025	4,146	4,226	3,985	
radius in mm	97	97	95	100	103	105	99	
run-up in sec	19							
run-down in sec. ²⁾	22							

4) Adapter set, 6-place, for conical 50 ml tubes with screw cap

35°



Angle rotor, 12-place,
Cat. No. 01613
 $n = 6,000 \text{ min}^{-1}$,
max. RCF 4,146

capacity in ml	1,6-5	4-7	8,5-10	15	15
dimensions Ø x L mm	12/13 x 75	13 x 100	16 x 100	17 x 100	17 x 120
 n=6,000 min ⁻¹ Cat.-No. 01613					
					
Cat.-No.	01054-A	01058	—	—	—
tubes per rotor	12	12	12	12	6
RCF	3,300	4,146			
radius in mm	86	103			
run-up in sec	13				
run-down in sec. ²⁾	15				



Cyto rotors, 4-place and 6-place suitable for C-28A more
information is available in a detailed cyto brochure.

2) Braked run down in sec.

Please make sure not to exceed the tubes
max. permissible RCF. For glass tubes the
max. RCF is 4,000



**BOECO MINI CENTRIFUGE
M-6**

BOECO MINI CENTRIFUGE M-6

This Mini-centrifuge is ideal for quick spin downs for Micro and PCR tubes and PCR strip. The M-6 is supplied with a 6 x 1,5/2,0ml angle rotor, a 2 x 8 x 0,2ml strip rotor and a slide rotor.

Operation of the centrifuge begins when the lid is closed. When opening the lid the rotor automatically decelerates and comes to a stop.

A rubber footplate keeps the unit stable and avoids vibration.

The M-6 is CE marked and has been manufactured under ISO 9001

Technical details

Max. RPM (speed) / RCF:	6,000 rpm / 2,000 x g
Noise level:	50 dB(A)
Power:	120 V to 240 V, 50/60 Hz
Dimensions in mm:(D/W/H)	175 x 148 x 118 mm
Net weight:	1,2 kg

Code	Description
BOE 8074000	BOECO Mini Centrifuge M-6, EU Plug
BOE 8074100	BOECO Mini Centrifuge M-6, US Plug
BOE 8074200	BOECO Mini Centrifuge M-6, UK Plug



BOECO CENTRIFUGE MICROSPIN 12

BOECO CENTRIFUGE MICROSPIN 12

is a compact bench-top microliter centrifuge for medical and biological research, molecular diagnostics, biochemistry, immunology and cell technologies. It can be used for extracting RNA/DNA samples, separation of cell suspensions and other micro quantitative analysis.

The microprocessor control provides precise control of the set parameters and a user-friendly interface allows a easy entry of parameters.

The brushless motor provides quite, vibration free performance, even at high speeds and a long product service life.

The angle rotor is made out of aluminium.

Due to the low voltage external power supply, the Microspin 12 can be used in cold rooms.

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » Entry of the running parameters via foil keypad
- » Speed display in RPM x 100, increment 100 rpm
- » Time t/min: 1 - 30 min, increment 1 min
- » Open lid key

Safety

- » Lid locking and holding device
- » Emergency lid lock release
- » Metal protective inserts and enclosures inside the body
- » See-through glass in the lid
- » Imbalance switch-off

The Microspin 12 conforms to safety regulations such as EN 61326, EN 61010 or the EU mark and all relevant EC standards and DIN norms and has been manufactured under ISO 9001:2015

Technical details

Max. RPM (speed) / RCF:	14,500 rpm / 12,400 x g
Noise level:	≤ 62 dB(A)
Power (external):	AC 100-240 V, 60 W/DC24 V, 2.5 A
Dimensions in mm: (D/W/H)	200 x 240 x 125 mm
Net weight:	3,4 kg

Code	Description
BOE 8075000	BOECO Micro centrifuge Microspin 12, 100-240 V, 50/60 Hz, with angle rotor for 12 x 1,5 / 2,0 ml microtubes and spin columns. And each 12 adapters for 0,2 and 0,5 ml microtubes

BOECO CENTRIFUGE MC-24

Powerful, space-saving, low-noise, reliable and microprocessor-controlled microlitre centrifuge with brushless frequency drive.

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » Entry of the running parameters via foil keypad
- » Speed display in RPM or RCF
 - RPM input from 200 to 10.000 in steps of 10, starting from 10.000 to the maximum speed in steps of 100
 - RCF input from 200 to 10.000 in steps of 1, starting from 10.000 to the maximum speed in steps of 10
- » Time t/min: 1 - 99 min. in steps of 1 min.,
Time t/sec: 1-59 sec. in steps of 1 sec.,
Continuous operation
- » Brake stage, selectable between fast and slow
- » Pulse key: For short centrifugation operations
- » Open lid key

Safety

- » Lid locking and holding device
- » Emergency lid lock release
- » Motor overheating protection
- » Imbalance switch-off
- » Deep metal rotor chamber (die-cast-zinc) to securely accommodate the rotor

The MC-24 conforms to safety regulations such as IEC 61010 or the EU mark and all relevant EC standards and DIN norms and has been manufactured under ISO 9001:2015

Technical details

Max. RPM (speed) / RCF: 14,000 rpm / 18,845 RCF
 Noise level: 59 dB(A)
 Emission / Immunity: EN / IEC 61326-1 class B / FCC class B
 Dimensions in mm: (H/W/D) 228 x 262 x 352
 Net weight: 11 kg



BOECO CENTRIFUGE MC-24

Code	Description
BOE 01203-13	BOECO centrifuge MC-24, 200-240 V, 50/60 Hz, without rotor



Angle rotor,
12-place
Cat. No. 01252-A
n = 14,000 min⁻¹,
max RCF 15,558

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
				
n = 14,000 min ⁻¹ Cat.-No. 01252-A	with high speeds we recommend to use adapter No. 02031			
Cat.-No.	—	02023	02024	—
tubes per rotor	12			
RCF	15,558			
radius in mm	71			
run-up in sec.	15			
run-down in sec. ²⁾	15			



Angle rotor, 18-place,
Cat. No. 01258-A
n = 14,000 min⁻¹,
max RCF 16,654

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
				
n = 14,000 min ⁻¹ Cat.-No. 01258-A	with high speeds we recommend to use adapter No. 02031			
Cat.-No.	—	02023	02024	—
tubes per rotor	18			
RCF	16,654			
radius in mm	76			
run-up in sec.	15			
run-down in sec. ²⁾	15			



Angle rotor, 24-place,
Cat. No. 01226-A
n = 14,000 min⁻¹,
max RCF 18,845

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
				
n = 14,000 min ⁻¹ Cat.-No. 01226-A	with high speeds we recommend to use adapter No. 02031			
Cat.-No.	—	02023	02024	—
tubes per rotor	24			
RCF	18,845			
radius in mm	86			
run-up in sec.	15			
run-down in sec. ²⁾	15			



Angle rotor,
18-place,
Cat. No. 01213-A
n = 14,000 min⁻¹,
max RCF 16,654

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0	1.5	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38	micro spin columns 11x38	
						
n = 14,000 min ⁻¹ Cat.-No. 01213-A	with high speeds we recommend to use adapter No. 02031					
Cat.-No.	—	02023	02024	—	—	—
tubes per rotor	18					
RCF	16,654					
radius in mm	76					
run-up in sec.	16					
run-down in sec. ²⁾	15					

The special raised rim of the rotor 01213-A enables centrifugation with open tube lids.



BOECO CENTRIFUGE M-240



BOECO CENTRIFUGE M-240R

BOECO CENTRIFUGES M-240 / M-240R

The M-240 and M-240R rank among the fastest centrifuges in their class – With a maximum speed of 15,000 rpm and an RCF of 21,382 they are not only fast, the M-240R also refrigerates quickly: to +4°C with the Fast Cool function in 10 to 15 minutes..

Even thermosensitive samples can be gently centrifuged thanks to highly reliable refrigeration. Best separation results are guaranteed with the smooth-running, high-performance motor featuring a maintenance-free frequency drive. With the optional autoclavable and aerosol-tight accessories, even infectious materials can be processed safely for both the user and the environment.

User-Friendliness

- » Automatic lid locking
- » Quick-entry foil keypad
- » Easy-to-read, digital display
- » Display of current parameter values
- » Select key for parameter selection
- » Impulse key for short centrifuging
- » Open lid key
- » RCF key
- » Twist knob to enter values
- » RPM in increments of 10
- » Running time in minutes, max. 99 min
- » Temperature in increments of 1°C (M-240R)
- » 4 programmable memories

Refrigeration (M-240R)

- » Infinitely variable setting from –10 °C to +40 °C
- » Fast Cool function in 10 - 15 min to +4 °C
- » Stand-by mode maintains the set temperature
- » Automatic refrigeration switch-off when the lid is opened

Safety

- » Lid dropping protection
 - » Lid locking and holding
 - » Emergency lid lock release
 - » Motor overheating protection
 - » Chamber overheating protection
 - » Imbalance switch-off
 - » Standstill indication
- with the refrigerated model M-240R the LED in the Open key lights up
with the M-240 the lid opens automatically after the rotor has come to a standstill

The M-240 / M-240R conform to safety regulations such as IEC 61010, all relevant EU standards and DIN norms and have been manufactured under ISO 9001:2015

Technical details

	M-240	M-240R
Max. RPM (speed) / RCF:	15,000 RPM / 21,382 RCF	
Noise level:	≤ 58 dB (A)	≤ 54 dB(A)
(dependent on rotor)		
Dimensions in mm (HxWxD):	260 x 275 x 344	260 x 281 x 533
Net weight:	11,5 kg	28 kg
Emission / Immunity:	EN / IEC 61326-1 / class B / FCC class B	

Code	Description
BOE 02400-13	BOECO centrifuge M-240, 200-240 V, 50/60 Hz, without rotor
BOE 02405-13	BOECO refrigerated centrifuge M-240R, 200-240 V, 50 Hz, without rotor

Rotors for M-240 and M-240 R



Angle rotor, 24-place
Cat. No. 02434
 $n = 15,000 \text{ min}^{-1}$,
max RCF 21,382
incl. biocontainment lid

capacity in ml	1.5	0.5/0.8	0.2 /0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
 $n = 15,000 \text{ min}^{-1}$ Cat.-No. 02434				
	with high speeds we recommend to use adapter No. 02031			
Cat.-No.	—	02023	02024	—
tubes per rotor	24			
RCF	21,382			
radius in mm	85			
run-up in sec.	20			
run-down in sec. ²⁾	29			
temperature °C ¹⁾	+4			



Angle rotor, 24-place
Cat. No. 02428
 $n = 15,000 \text{ min}^{-1}$,
max RCF 21,382
incl. bioseal lid

capacity in ml	1.5	0.5/0.8	0.2 /0.4	2.0	1.5	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38	micro spin columns 11x38	
 $n = 15,000 \text{ min}^{-1}$ Cat.-No. 02428						
	with high speeds we recommend to use adapter No. 02031				with high speeds we recommend to use adapter No. 02031	
Cat.-No.	—	02023	02024	—	—	—
tubes per rotor	24					
RCF	21,382					
radius in mm	85					
run-up in sec.	20					
run-down in sec. ²⁾	28					
temperature °C ¹⁾	+4					

The special raised rim of the rotor 02428 enables centrifugation of tubes with open lids. The rim supports the lids so they will not rip off during centrifugation. Centrifugation with open tube lids is performed for example when spinning tubes with filter elements, so called „spin columns“



Angle rotor, 30-place,
Cat. No. 02437
 $n = 15,000 \text{ min}^{-1}$,
max RCF 21,328
incl. bioseal lid.

capacity in ml	1.5	0.5/0.8	0.2 /0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
 $n = 15,000 \text{ min}^{-1}$ Cat.-No. 02437				
	with high speeds we recommend to use adapter No. 02031			
Cat.-No.	—	02023	02024	—
tubes per rotor	30			
RCF	21,328			
radius in mm	85			
run-up in sec.	22			
run-down in sec. ²⁾	30			
temperature °C ¹⁾	+4			



Optional for rotor 02437 and 02434

Lid (Cat. No. 02435)
with bio-containment
autoclavable,
phenol-resistant



BOECO CENTRIFUGE U-320



BOECO CENTRIFUGE U-320R

BOECO CENTRIFUGES U-320 / U-320R

Because of their comprehensive range of accessories, the U-320 and U-320R centrifuges are the perfect universal centrifuges for routines in basic research and R&D laboratories of the pharmaceutical and biotechnical industry. The microprocessor controlled centrifuges have a brushless frequency drive (no carbon brushes) and a motorized lid locking.

Performance

- » High RCF
- » Extremely short run-up and run-down times

Design

- » Metal housing, metal lid
- » Stainless steel centrifugation chamber
- » Viewing port in the lid

Refrigeration (U-320R)

- » Infinitely variable setting from -20°C to $+40^{\circ}\text{C}$
- » Fast cool function

User-Friendliness

- » Automatic lid locking
- » Easily exchangeable rotors
- » 10 programmable memories
- » 9 acceleration and braking ramps, or unbroken run down time

Safety

- » Lid locking and holding during rotor run
- » Emergency lid lock release
- » Motor overheating protection
- » Chamber overheating protection (with U-320R)
- » Imbalance switch-off
- » Automatic rotor recognition
- » Lid dropping protection

Controls and displays

- » During centrifugation the actual values of the parameters are indicated
- » Change-over RPM/RCF: by entering the rotor radius r/mm the Centrifuge will calculate/indicate speed or RCF.
- » Time preselection in steps of minutes and seconds / continuous operation
- » Temperature $T/^{\circ}\text{C}$: Input in increments of 1°C
- » Impulse key: For short centrifugation operations

The U-320 / U-320R conform to safety regulations such as IEC 61010 or the EC mark and all relevant EU standards and DIN norms and have been manufactured under ISO 9001:2015

Technical details

	U-320	U-320 R
Max. Capacity:	4 x 200 ml, 6 x 94 ml	
Max. RPM (speed) / RCF:	15,000 RPM / 21,382 RCF	
Noise level:	$\leq 68 \text{ dB (A)}$	$\leq 58 \text{ dB(A)}$
(dependent on rotor)		
Dimensions in mm (HxWxD):	346 x 395 x 520	346 x 401 x 695
Net weight:	31 kg	52 kg
Emission / Immunity:	EN IEC 61326-1, class B / FCC Class B	

Code	Description
BOE 01401-13	BOECO centrifuge U-320, 200-240 V, 50/60 Hz, without rotor
BOE 01406-13	BOECO refrigerated centrifuge U-320R, 200-240 V, 50 Hz 240 V, 60 Hz, without rotor

Swing-out rotor 01624, 4-place,
illustrated with
carriers 01369
n= 4,000 min⁻¹,
max. RCF 2,665
max. cap. 4 x 100 ml.



Swing-out rotor,
No. 01624, 4-place,
n= 4,000 min⁻¹,
max. RCF 2,665
for max. 4 x 100 ml

capacity in ml	5	4-7	9	9	15	1,6 - 7	15	20	25	45	50
dimensions Ø x L mm	12/13x75	13 x 100	14 x 100	14 x 100	17 x 100	12/13x75 16 x 75	17 x 100	21 x 100	24 x 100	31 x 100	34 x 100
											
n=4,000 min ⁻¹ Cat.-No. 01624											
Cat.-No.	01372	01739	01370	01741	01369	01742	01742	01346	01745	01345	01746
tubes per rotor	68	28	20	40	16	28	28	8	8	4	4
RCF	2,164	2,451	2,308	2,415	2,308	2,325	2,415	2,361	2,451	2,361	2,451
radius in mm	121	137	129	135	129	130	137	132	137	132	137
run-up in sec	20	22		20		22		20			
run-down in sec. ²⁾						25					
temperature °C ¹⁾		- 17		- 15	- 17	- 15	- 15	- 15	- 15	- 17	- 15

1) Lowest attainable temperature in the U-320 R at max. speed.


2) braked run-down

Please take care not to exceed the tubes' max. permissible RCF!

capacity in ml	1	3	1,6-7	4-10	9/15	25	30	50	50	85	100	15	50	1,6 - 7	4 - 10
dimensions Ø x L mm	6x45 Rhesus	10 x 60	13 x 75/100	16x75/100	14/17 x 100	24 x 100	26 x 95	29 x 107	34 x 100	38 x 106	44 x 100	17 x 120	29 x 115	13x75/100	16x75/100
															
Cat.-No.	01339	01343	01383	01348	01329	01330	04417	04416	01331	01396	00761	01347	01384	01383	01348
tubes per rotor	108	36	20	16	16	4	4	4	4	4	4	4	4	20	16
RCF	2,594	2,630	2,558	2,522	2,540	2,433	2,451	2,630	2,415	2,612	2,558	2,665	2,665	2,558	2,522
radius in mm	145	147	143	141	142	136	137	147	135	146	143	149	149	143	141
run-up in sec															
run-down in sec. ²⁾															
temperature °C ¹⁾															



Swing-out rotor, No. 01494
4-place,
n= 5,000 min⁻¹,
max. RCF 4,193
illustrated with buckets
01427

capacity ml	1.5/2.0	1	3	5	6	7	9	15	25	50	15	25	30	50
dimensions Ø x L mm	11 x 38	6 x 45 Rhesus	10 x 60	13 x 75	12 x 82	12 x 100	14 x 100	17 x 100	24 x 100	34 x 100	17 x 120	25 x 90	25 x 110	29 x 115
														
n= 5,000 min ⁻¹ Cat.-No. 01494														
Cat.-No.	05277	01357	01327	01732	05229	05230	05237	05231	05232	05233	05275	01731	05272	05276
tubes per rotor	36	120	48	32	48	48	24	24	8	4	4	8	4	4
RCF	4,109	4,081	4,053	4,025	4,053			3,941			4,165	3,969	4,025	4,053
radius in mm	147	146	145	144	145			141			149	142	144	145
run-up in sec								30						
run-down in sec. ²⁾								32						
temperature °C ¹⁾								- 7						

3) When using these tubes, bucket 01427 cannot be closed with lid 01421



Swing-out rotor, No. 01494
4-place,
n= 5,000 min⁻¹,
max. RCF 4,193
illustrated with buckets 01425

capacity ml	1.5/2.0	1	3	2,6-7	5/6/7	9/15	25	50	100	15	50	50	4 - 10
dimensions Ø x L mm	11 x 38	6 x 45 Rhesus	10 x 60	11x100	12x75-100	14/17x100	24 x 100	34 x 100	44 x 100	17 x 120	29 x 115	29 x 115	16 x 75/100
													
Cat.-No. 01425													
Cat.-No.	01444	01432	01433	01438	01434	01431	01435	01436	01437	01442	01443	01737	01441
tubes per rotor	36	144	56	28	48	28	8	4	4		4		28
RCF		3,969			3,913				3,801		4,081		3,913
radius in mm	139	142			140				136		146		140
run-up in sec								30					
run-down in sec. ²⁾								32					
temperature °C ¹⁾								- 10					

capacity ml	1.5/2.0	1	3	5	6/7	9/15	25	50	100	10	30	50	85	15	50	12	25	30	50
dimensions Ø x L mm	11 x 38	6 x 45 Rhesus	10x60	13x75	13x82/100	14/17x100	24 x 100	34 x 100	44 x 100	16x80/100	26x95	29x107	38x106	17x120	29x115	17x100	25 x90	25x110	29x115
 Lid No. 01492 biocontainment ⁵⁾																			
Carrier Cat.-No. 01495																			
Cat.-No.	01351	01339	01343	01383	01383	01329	01330	01331	00761	01348	04417	04416	01396	01347	01384	06311	01363	01365	06318
tubes per rotor	20	108	36	20	20	16	4	4	4	16	4	4	4		4				
RCF	3,857	4,081	4,137	4,025	4,025	3,997	3,829	3,801	4,025	4,025	3,857	4,137	4,109		4,193		3,689		4,193
radius in mm	138	146	148	144	144	143	137	136	144	144	138	148	147		150		132		150
run-up in sec										30									
run-down in sec. ²⁾										32									
temperature °C ¹⁾										- 10									






Swing-out rotor 01324, 4-place,
 illustrated with suspension 01398
 and adapter 01483
 n = 4,500 min⁻¹,
 max. RCF 3,260



Swing-out rotor 01324, 4-place,
 illustrated with
 carrier 01490 and lids 01492
 n = 4,500 min⁻¹,
 max. RCF 3,328
 for max. 4 x 100 ml

capacity ml	9	15	2,6-3,4	4-5,5	9-10	10	4-7	15	50	12	50
dimensions Ø x L mm	14x100	17x100	13x65	15x75	16x92	15x102	16 x 75	17x120	29x115	17x100	29x115
 Carrier Cat.-No. 01398											
Cat.-No.	01482-A	01486	01482-A	01482-A	01482-A	01483-A	01484	01482-A	01484	01482-A	01484
tubes per rotor	16	20	16	16	16	16	16	4	16	4	16
RCF	3,192	3,147	2,875	3,192	3,034	3,305	3,260	3,192	3,260	3,192	3,260
radius in mm	141	139	127	141	134	146	144	141	144	141	144
run-up in sec						27					
run-down in sec. ²⁾						30					
temperature °C ¹⁾						- 6					

capacity ml	1.5/2.0	1	3/4	5	6/7	9/15	25	50	100	4-10	30	50	85	15	50	12	25	30	50	
dimensions Ø x L mm	11 x 38	5 x 45 Rhesus	10x60/88	12/13x75	13x82/100	14/17x100	24 x 100	34 x 100	44 x 100	16x75/100	26x95	29x107	38x106	17x120	29x115	17x100	25 x90	25x110	29x115	
lid No. 01492 biocontainment ⁵⁾																				
																				
Carrier Cat.-No. 01490																				
Cat.-No.	01351	01339	01343	01383	01383	01329	01330	01331	00761	01348	04417	04416	01396	01356	01347	01384	06311	01363	01365	06318
tubes per rotor	20	108	36	20	20	16	4	4	4	16	4	4	4	12	4					
RCF	3,056	3,237	3,283	3,192	3,192	3,170	3,034	3,011	3,192	3,147	3,056	3,283	3,260	3,328			2,920		3,328	
radius in mm	135	143	145	141	141	140	134	133	141	139	135	145	144	147			129		147	
run-up in sec											27									
run-down in sec. ²⁾											30									
temperature °C ¹⁾											- 6									

90°



Swing-out rotor, 8-place,
 n = 4,000 min⁻¹,
 max. RCF 2,415,
 for 8 x 15 ml,
 stainless steel,
 with suspensions No. 01644, PA,
 fibreglass reinforced.

capacity in ml	5	10	10	15
dimensions Ø x L mm	12/13x75	17 x 70	13 x 100	17 x 100
 n = 4,000 min ⁻¹ Cat.-No. 01611				
Cat.-No.	01131-A	01132-A	01643	01644
tubes per rotor	8	8	8	8
RCF		1,914		2,415
radius in mm		107		135
run-up in sec			20	
run-down in sec. ²⁾			20	
temperature °C ¹⁾			-16	

75°



Swing-out rotor, 12-place,
 n = 5,000 min⁻¹,
 max. RCF 4,193,
 for 12 x 15 ml, stainless steel,
 with suspensions No. 01621, PA,
 fibreglass reinforced.


capacity in ml	5	10	15
dimensions Ø x L mm	12/13 x 75	17 x 70	17 x 100
 n = 5,000 min ⁻¹ Cat.-No. 01628			
Cat.-No.	01127-A	01122	01621
tubes per rotor	12	12	12
RCF	3,494	3,522	4,193
radius in mm	125	126	150
run-up in sec		16	
run-down in sec. ²⁾		16	
temperature °C ¹⁾		-15	-10

capacity ml	1.5/2.0	5	5-7	1,6-7	9/15	25	50	85	100	125/150	200	30	50	15		50	12	25/30	50
dimensions Ø x L mm	11 x 38	17x59	12x75/100	13x75/100	14/17x100	24 x 100	34 x 100	38x101/6	44 x 100	51x100/116	56 x 112	26 x 95	29 x 107	17 x 120		29 x 115	17 x 100	25x90/110	29x115
lid No. 01561 biocontainment ⁵⁾ 																			
																			
Carrier Cat.-No. 01560																			
Cat.-No.	01571	01593	01589	01589	01588	01573	01574	01575	01576	01594	-	01585	01586	01577	01595	01579	01582	01582	01583
tubes per rotor	56	16	28	28	20	4	4	4	4	4	4	4	4	8	12	4	16	4	
max. RCF	^{3,328} 3,328	3,328	3,215	3,215	3,215	3,056	3,147	3,260	3,147	3,328	3,328	3,260	3,260	3,328			3,260	3,328	
radius in mm	147/103	147	142	142	142	135	139	144	139	147	147	144	144	147			144	147	
run-up in sec	28																		
run-down in sec. ²⁾	31																		
temperature °C ³⁾	- 8																		



Swing-out rotor, 01554, 4-place,
illustrated with
carrier 01560 and lids 01561
n= 4,500 min⁻¹,
max. RCF 3,328
for max. 4 x 200 ml

Swing-out rotor 01554,
4-place,
illustrated with
carrier 01563

capacity in ml	12	15	50	50
dimensions Ø x L mm	17 x 100	17 x 120	29 x 115	29 x 115
 Carrier Cat.-No. 01563				
Cat.-No.	01592	01592	-	-
tubes per rotor	8			
RCF	3,260			
radius in mm	144			
run-up in sec	28			
run-down in sec. ²⁾	31			
temperature °C ³⁾	-8			



Swing-out rotor, 6-place,
n= 4,000 min⁻¹,
RCF 2,701,
for 6 x 50/15ml Falcon tubes,
stainless steel,
with suspensions, PA,
fiberglass reinforced.

capacity in ml	15	50
dimensions Ø x L mm	17 x 120	29 x 115
 n=4,000 min ⁻¹ Cat.-No. 01619		
Cat.-No.	01462-A	-
tubes per rotor	6	
RCF	2,701	
radius in mm	151	
run-up in sec	20	
run-down in sec. ²⁾	22	
temperature °C ³⁾	- 15	



Swing-out rotor, 8-place,
n= 5,000 min⁻¹,
RCF 3,857,
for 8 x 50/15 ml,
stainless steel, with
suspensions, aluminium.

capacity in ml	15	50
dimensions Ø x L mm	17 x 120	29 x 115
 n=5,000 min ⁻¹ Cat.-No. 01617		
Cat.-No.	01462-A	-
tubes per rotor	8	
RCF	3,857	
radius in mm	138	
run-up in sec	20	
run-down in sec. ²⁾	19	
temperature °C ³⁾	- 10	



Swing-out rotor,
24-place, with bioseal, phe-
nol-resistant lid
n= 13,000 min⁻¹,
RCF 18,127

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
 incl. biosal lid n=13,000 min ⁻¹ Cat.-No. 01555				
Cat.-No.	-	02023	02024	-
tubes per rotor	24			
RCF	18,327			
radius in mm	97			
run-up in sec	36			
run-down in sec. ²⁾	31			
temperature °C ³⁾	3			



Swing-out rotor,
2-place, n=4,000 min⁻¹,
RCF 2,218
for microtitre plates,
aluminium, coated,
with suspensions No. 01453-A,
stainless steel.

	microtitre plate	culture plate	deep well plate	MS	QP	Microtest plate (Terasaki)	PCR plate 96 wells	PCR strips 0,2
 n=4,000 min ⁻¹ Rotor Cat.-No. 01460								
Cat.-No.	01453-A							01453-A + 01485
plates per rotor	10	8	6	2	2	4	2	24 x 8
RCF	2,218							
radius in mm	124							
run-up in sec	40							
run-down in sec. ²⁾	45							
temperature °C ³⁾	-6							

1) Lowest attainable temp. in precooled refrigerated centrifuges at max. speed.

2) Rund down in sec. braked

Please make sure not to exceed the tubes max. permissible RCF. For glass tubes the max. RCF is 4,000

45°



Angle rotor,
Cat. No. 01418
8-place
 $n = 4,500 \text{ min}^{-1}$
max. RCF 3,305
illustrated with adapters 01467

capacity in ml	4-7	15	15	50	12	50	50
dimensions Ø x L mm	13 x 100	17 x 100	17 x 120	29 x 115	17 x 100	29 x 115	29 x 107
$n = 4,500 \text{ min}^{-1}$ Cat.-No. 01418	+ 00716	+ 00716	+ E2109	+ E2110	+ 00716		
Cat.-No.	01467	01467	01467	01468	01467	01468	
tubes per rotor	32	32	32	8	32	8	
RCF	3,305	3,215	3,283	3,147	3,215	3,147	
radius in mm	146	142	145	139	142	139	
run-up in sec	30						
run-down in sec. ²⁾	31						
temperature °C ¹⁾	-11						

45°



Angle rotor,
Cat. No. 01627
18-place, with bioseal, phenol-resistant lid
 $n = 14,150 \text{ min}^{-1}$,
RCF 22,161,
for 5 ml microtest tubes

capacity in ml	5,0 ml
dimensions Ø x L mm	17 x 59
$n = 14,500 \text{ min}^{-1}$ Cat.-No. 01627	
Cat.-No.	
tubes per rotor	18
RCF	22,161
radius in mm	
run-up in sec	35
run-down in sec. ²⁾	32
temperature °C ¹⁾	2

35°



Angle rotor,
Cat. No. 01556
6-place,
 $n = 9,000 \text{ min}^{-1}$,
max. RCF 10,595

capacity in ml	10	10-15	30	50	50/75	85	15	50
dimensions Ø x L mm	16 x 80	17 x 100	26 x 95	29 x 107	34 x 100 35 x 105	38 x 106	17 x 120	29 x 115
$n = 9,000 \text{ min}^{-1}$ Cat.-No. 01556								
Cat.-No.	01477	01478	01447	01446	01463	—	01466	01454
tubes per rotor	12	6	6	6	6	6	6	6
RCF	10,414	10,052	9,690	10,142	10,414	10,595	10,052	
radius in mm	115	111	107	112	115	117	111	
run-up in sec	30							
run-down in sec. ²⁾	30							
temperature °C ¹⁾	- 11							

1) Lowest attainable temp. in precooled refrigerated centrifuges at max. speed

2) Rund down in sec. braked

Please make sure not to exceed the tubes max. permissible RCF. for glass tubes the max. RCF is 4,000

35°



Angle rotor,
Cat. No. 01613
12-place,
 $n = 6,000 \text{ min}^{-1}$,
max. RCF 4,146

capacity in ml	5	15	15
dimensions Ø x L mm	12/13 x 75	17 x 100	17 x 120
$n = 6,000 \text{ min}^{-1}$ Cat.-No. 01613			
Cat.-No.	01054A	—	—
tubes per rotor	12	12	6
RCF	3,300	4,146	
radius in mm	82	103	
run-up in sec	15		
run-down in sec. ²⁾	15		
temperature °C ¹⁾	- 16		

35°



Angle rotor,
Cat. No. 01615
12-place,
 $n = 12,000 \text{ min}^{-1}$, max.
RCF 16,582

capacity in ml	5	15	15
dimensions Ø x L mm	12/13 x 75	17 x 100	17 x 120
$n = 12,000 \text{ min}^{-1}$ Cat.-No. 01615			5)
Cat.-No.	01054A	—	01647
tubes per rotor	12	12	6
RCF	13,201	16,582	15,455
radius in mm	82	103	93
run-up in sec	40		
run-down in sec. ²⁾	40		
temperature °C ¹⁾	-2		

50°



Angle rotor,
Cat. No. 01552
24-place,
incl. bioseal lid,
phenol resistant
 $n = 16,000 \text{ min}^{-1}$, max.
RCF 24,900

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
incl. bioseal lid $n = 16,000 \text{ min}^{-1}$ Cat.-No. 01552				
Cat.-No.	—	02023	02024	—
tubes per rotor	24			
RCF	24,900			
radius in mm	87			
run-up in sec	30			
run-down in sec. ²⁾	29			
temperature °C ¹⁾	2			

45°



Angle rotor,
Cat. No. 01553
30-place,
incl. bioseal lid, phenol
resistant
 $n = 14,150 \text{ min}^{-1}$
max RCF 21,713

capacity in ml	1.5	0.5/0.8	0.2/0.4	2.0
dimensions Ø x L mm	11x38	8x30/45	6x18/45	11x38
incl. bioseal lid $n = 14,150 \text{ min}^{-1}$ Cat.-No. 01553				
Cat.-No.	—	02023	02024	—
tubes per rotor	30			
RCF	21,713			
radius in mm	97			
run-up in sec	35			
run-down in sec. ²⁾	32			
temperature °C ¹⁾	-1			

Cyto rotors, suitable for U-320 and U-320R are available.
More informations are available in a detailed cyto brochure.

