

ELECTROCHEMISTRY

BOECO PORTABLE PH/ORP/TEMP METER MODEL PT-380

- » Simultaneous displays pH or mV and temperature.
- » Convenient calibration with automatic buffer recognition of European and US buffer sets. Calibration data is stored in memory and is ready for use on power up.
- » Automatic or manual temperature compensation
- » Automatic lock mode and end point sensing are available to lock in stable readings.
- » 50 data set reviewable memory.
- » Automatic shut off function (30 minutes of non-use)
- » Battery life 1000 hours
- » Low battery indicator
- » IP65 waterproof case

The PT-380 will be delivered incl. the following standard accessories:
1 x ATC probe 6000AST, each 1 x 100 ml BOECO Buffer solution pH 4,01, pH 7,00, 1 x 9 V battery, 1 x operating manual, 1 x carrying case

Specification:

pH

Range	Resolution	Accuracy
-2 to 16,00 pH	0,01 pH	$\pm 0,01 \pm 1$ digit

mV

Range	Resolution	Accuracy
-1999 to 1999 mV	1 mV	$\pm 0,1 \%$

Temperature

Range	Resolution	Accuracy
-10,0 to 120,0 °C	0,1 °C	$\pm 0,5 \%$

pH buffer recognition:	US (4,01, 7,00, 10,01) NIST (4,00, 6,86, 9.18) user selectable
pH electrode offset Recognition:	± 90 mV at pH 7,00 or 6.86
pH electrode slope Recognition:	$\pm 30\%$ at pH 4,00, 4,01, 9,18 or 10,01
pH temp. compensation:	Auto / manual -10,0 to 120 °C
Input Impedance:	10^{12} ohms
Temperature sensor:	Thermistor, 10K ohms at 25°C
RS 232 interface:	no
Power requirement:	9 Volt battery
Dimensions (LxWxH):	198 x 70 x 37 mm
Weight:	0,26 kg (1 x 9V Battery included)

Code	Description
BOE 5190380	Portable pH/ORP/Temperature meter, model PT-380 in carrying case with standard accessories without electrode



BOECO PORTABLE PH/ORP/TEMP METER
MODEL PT-380



BOECO ELECTRODES

The electrodes are not included with the pH meters and have to be ordered separately:

Code	Description
BOE 5190600	Basic pH combination electrode, BA ECO plastic PC shaft, gel electrolyte, 0...14 pH, 0...80°C, with BNC plug, 1m cable, glass sensor
BOE 5095695	Basic pH combination electrode BA 25, Noryl plastic shaft, gel electrolyte, 0...14 pH, -5...80°C, with BNC plug, 1m cable, fibre diaphragm
BOE 5095626	Basic pH combination electrode BA 17, glass shaft, liquid electrolyte, 0...14 pH, 0...100°C, with BNC plug, 1m cable. With leak proof refill opening, platinum diaphragm



BOECO ELECTRODES

BOECO PH/ORP/TEMP BENCH TOP METER MODEL BT-700

- » LCD display with backlight showing pH / ORP and temperature readings
- » Up to 5 point calibration for pH and one point calibration for and ORP
- » Automatic buffer recognition (NIST and USA)
- » Automatic or manual temperature compensation
- » Bluetooth function to connect to tablets
App name **BOECO E-Chem BT-700 (App Store / Googleplay)**
- » When the unit is connected to a bluetooth device, the user can store data into the device that meets GLP requirements
- » AC adaptor or battery power (low battery indicator)

The BT-700 will be delivered incl. the following standard accessories:
1 x ATC probe, each 1 x 500 ml Buffer solution pH 4,01, pH 7,00
1 x AC adaptor, 1 x operating Manual, 1 x flexible electrode holder.
6 x 1,5 V AAA batteries

Specification:

pH

Range

-2 to 16,00 pH

Resolution

0.01 pH

Accuracy

± 0,01

mV

Range

-1999,9 to 1999,9 mV

Resolution

0,1 mV

Accuracy

A 0,05 % full scale

Temperature

Range

-10 to 120,0°C

Resolution

0,1°C

Accuracy

±0,2°C

pH buffer recognition:

US (1,68, 4,01, 7,00, 10,01, 12,46) or
NIST (1,68, 4,00, 6,86, 9,18, 12,46)
user selectable

Buffer temp. range

0 - 60,0 °C

pH calibration

Up to 5 points

ORP calibration:

1 point Offset ±150mV

ATC :

Auto / manual -10,0 to 120°C

Input impedance:

>1x10¹² ohms

Connectivity:

Bluetooth

Memory:

When the unit is connected to a bluetooth device, the user can store data into the device that meets GLP requirements

Temperature sensor:

Thermistor, 10K ohms at 25°C

Power requirement:

6 x 1,5 Volt AAA Alkaline batteries or
AC adaptor

Case:

IP54 waterproof

Dimensions (LxWxH):

210 x 150 x 45 mm

Weight:

0,43 kg

Code

BOE 5196700

Description

Bench Top pH/mV/Temp Meter, Model BT-700,
AC adaptor with attachable EURO/US plug
with standard accessories, without electrode



BT-700

BOECO MULTIPARAMETER PH/ORP/CONDUCTIVITY/TDS/ SALINITY/RESISTIVITY/TEMPERATURE BENCH TOP METER MODEL MBT-700

- » LCD display with backlight showing pH / ORP or Conductivity / TDS / Salinity and temperature readings
- » Two channel measurement allows measuring pH/ORP and Conductivity/TDS/ Salinity simultaneously
- » Up to 5 point calibration for pH and one point calibration for conductivity and ORP
- » Automatic or manual temperature compensation
- » Automatic buffer recognition (NIST and USA)
- » Bluetooth function to connect to tablets.

App name: BOECO E-Chem MBT-700

- » When the unit is connected to a bluetooth device, the user can store data into the device that meets GLP requirements.

The MBT-700 will be delivered incl. the following standard accessories:
1 x ATC probe, each 1 x 500 ml Buffer solution pH 4,01, pH 7,00
1 x AC adaptor, 1 x operating manual, 1 x flexible electrode holder, 1 x 4 wire Conductivity cell 101C

Specification:

Conductivity K = 0,475

Range	Resolution	Accuracy
0,0 to 474,9µS/cm	0,1µS/cm	±0,5% Full Scale
475 to 4749µS/cm	1µS/cm	±0,5% Full Scale
4,75 to 47,49mS/cm	0,01mS/cm	±0,5% Full Scale
47,5 to 200,0mS/cm	0,1mS/cm	±0,5% Full Scale

Conductivity K = 0,1

Range	Resolution	Accuracy
0.00 to 99,99µS/cm	0,01µS/cm	±0,5% Full Scale
100 to 200µS/mS	0,1µS/cm	±0,5% Full Scale

TDS

Range	Resolution	Accuracy
0,00mg/l to 200,0g/l	0,01/0,1/1mg/l 0.01/0,1 g/l	±0,5% Full Scale

Salinity

Range	Resolution	Accuracy
0,0 to 80,0 ppt	0,1 ppt	±0,5 % Full Scale

pH

Range	Resolution	Accuracy
-2,00 to 16,00 pH	0,01 pH	±0,01pH

mV

Range	Resolution	Accuracy
-1999,9 to 1999,9 mV	0,1 mV	±0,05% Full Scale

Temperature

Range	Resolution	Accuracy
-10,0 to 120,0°C	0,1°C	±0,2°C

pH buffer recognition:	US (1,68 4,01, 7,00, 10,01, 12,46 or NIST (1,68, 4,00, 6,86, 9,18, 12,46)
mV Offset	±150 mV
pH calibration:	
Up to 5 points	
Conductivity Calibration:	1 point in each range
ATC :	Auto / manual -10,0 to 120°C
Input impedance:	>1x10 ¹² ohms
Temperature sensor:	Thermistor, 10K ohms at 25°C
Memory:	When the unit is connected to a bluetooth device, the user can store data into the device that meets GLP requirements
pH electrode connection:	BNC
Conductivity cell connection:	8 PIN connector
Connectivity:	Bluetooth
Power requirement:	6 x 1,5 Volt AAA Alkaline batteries or AC adaptor
Case:	IP54 waterproof
Dimensions (LxWxH):	210 x 150 x 45 mm
Weight (net):	approx. 0,43 kg

Code

BOE 5197700

Description

Bench Top pH/mV/Ion/Temp Meter, Model MBT-700,
AC adaptor, with standard accessories as above mentioned,
without electrode





PH/TEMP. TESTER PT-70 WITH
REPLACEABLE ELECTRODE



ELECTRODE MODULE

PHBOECO /TEMP. POCKET TESTER PT-70

with replaceable electrode

- » Large display screen - displays pH and temperature at the same time
- » 1, 2 or 3 point calibration, with automatic buffer recognition of US and NIST buffer sets
- » Readings are automatically compensated for temperature (ATC)
- » Electrode efficiency display
- » Replaceable electrode module ensures extended usefulness
- » IP67 water-tight housing
- » Auto power off after 10 minutes of inactivity
- » Battery life over 200 hours

Specification:

Modes:	pH, °C
Ranges:	pH 0 to 14 pH Temp. -9,9...99,9 °C
Resolution:	pH 0,01 pH Temp. 0,1 °C
Accuracy:	pH $\pm 0,02$ pH ± 1 digit Temp. $\pm 0,3$ °C ± 1 digit
Temperature compensation:	Auto from -9,9 to 99,9°C
pH buffer recognition:	US (pH 4.01, 7.00, 10.01) NIST (pH 4.00, 6.86, 9.18)
Buffer temp range:	0,0 - 60 °C
Input impedance:	> 10^{12} ohms
pH calibration:	1, 2 or 3 point calibration
pH electrode offset recognition:	± 90 mV at pH 7,00 $\pm 98,3$ mV to $-81,7$ mV at pH 6,86 $\pm 30\%$ at pH 4,00; 4,01; 9,18 and 10,01
pH electrode slope recognition:	9,18 and 10,01
Power:	4 x LR44 button cell batteries
Dimensions :	193 x 44 x 25 mm
Weight :	0,105 kg (incl. batteries)

Code	Description
BOE 5190070	PH/Temp. Tester PT-70
BOE 5190071	Spare pH electrode module PT-70-1 for PT-70

TECHNICAL BUFFER SOLUTIONS

In square plastic bottles, PE, 500 ml, labeled with an individual batch no. on the bottles, traceable to SRM of NIST

Code	Description
BOE 104000	pH 4,00 (20°C), 500 ml
BOE 107000	pH 7,00 (20°C), 500 ml
BOE 610000	pH 10,00 (20°C), 500 ml
BOE 104004	pH 4,00 (20°C), 500 ml, red colour coded
BOE 107006	pH 7,00 (20°C), 500 ml, green colour coded
BOE 610008	pH 10,00 (20°C), 500 ml, blue colour coded

CONDUCTIVITY CALIBRATION SOLUTIONS

In square plastic bottles, PE, 250 ml, labeled with an individual batch no. on the bottles, traceable to PTB and NIST

Code	Description
BOE 300141	1,413 mS/cm KCL 0,01 mol/l (25°C), 250 ml
BOE 301288	12,88 mS/cm KCL 0,1 mol/l (25°C), 250 ml
BOE 311180	111,8 mS/cm KCL 1 mol/l (25°C), 250 ml

ELECTROLYTE SOLUTION

In square plastic bottles, PE, 500 ml, labeled with an individual batch no. on the bottles

Code	Description
BOE 400300	Potassium chloride 3 mol/l, 500 ml

PH INDICATORS

pH-Fix is the most popular indicator stick for all purposes. The indicator dyes are chemically bound to the cellulose fibres, avoiding bleeding even in strong alkaline samples. Presentation: Box of 100 sticks 6 x 85 mm

Code	Description
M-N 92110	pH-Fix 0-14, pH Graduation 1,0

The budget priced universal indicator papers can be used for most standard applications. For each pH-value these papers show a single colour which can be matched with the colour scale at an interval of 1 pH-unit. Presentation: Reel of 5 m length and 7 mm width

Code	Description
M-N 90204	pH-Universal Indicator Paper, pH 1-14, pH Graduation 1,0/2,0



PH INDICATORS

BOECO PORTABLE DO/TEMP. METER MODEL DO-580

- » Simultaneous display of dissolved oxygen and temperature measurements
- » Automatic temperature compensated (ATC) dissolved oxygen readings
- » User selectable salinity and pressure compensated dissolved oxygen readings
- » Works with accurate and reliable galvanic dissolved oxygen probes
- » 50 data set reviewable memory
- » Automatic shut off function (30 minutes of non-use)
- » Battery life approx. 200-500 hours
- » Low battery indicator
- » IP65 waterproof case

Specification:

Dissolved Oxygen (ppm)

Ranges	0,00 to 20,00 ppm (mg/L)
Resolution	0,01 ppm (mg/L)
Accuracy	±2 % of the reading or ±0,2 ppm

Dissolved Oxygen (%)

Ranges	0,0 to 200,0 %
Resolution	0,1 %
Accuracy	±2 % of the reading or ±0,2 air saturation

Temperature

Ranges	-6 to 46,0 °C
Resolution	0,1°C
Accuracy	±0,3 °C ±1 digit

Pressure compensation: 600 to 1100 mBar (450 to 825 mmHg)

Salinity compensation: From 0,0 to 40,0 ppt

Electrode type: Galvanic

Temperature sensor: Thermistor, 10K ohms, at 25 °C

Calibration backup: Yes

Automatic temp. comp: Yes

Power: 9 Volt battery

Size (LxWxD): 198 x 70 x 37 mm

Weight: 1,26 kg (1 x 9V Battery included)

The DO-580 will be delivered incl. the following standard accessories:
1 x Watertight dissolved oxygen probe LD-900-11, 1 x 30 ml Galvanic O2 Fill Solution, 1 x 9 V battery, 1 x Operating manual, 1 x carrying case

Code	Description
BOE 5190580	Portable DO/Temperature Meter, Model DO-580 in carrying case with dissolved oxygen probe LD-900-11



BOECO PORTABLE
DO/TEMP METER
MODEL DO-580





BOECO PORTABLE CONDUCTIVITY/
TDS/SALINITY/TEMP METER
MODEL CT-480



BOECO PORTABLE CONDUCTIVITY/TDS SALINITY/TEMP. METER MODEL CT-480

- » Simultaneous displays of conductivity, salinity or TDS with temperature measurements.
- » Convenient one point calibration. Calibration data is stored in memory and is ready for use on power up.
- » Adjustable TDS coefficient, reference temperature and temperature coefficient
- » Uses one conductivity cell for conductivity, salinity and TDS measurement
- » Accepts 4-wire conductivity cells with $k=0,475$ cell constant and 2-wire $K=0,1$ cell constant for improved flexibility and accuracy
- » 50 data set reviewable memory
- » Automatic shut off function (30 minutes of non-use)
- » Battery life approx. 200-500 hours
- » Low battery indicator
- » IP65 waterproof case

Specification:

Conductivity $K = 0,475$

Range	Resolution	Accuracy
0,0 to 475 $\mu\text{S/cm}$	0,1 $\mu\text{S/cm}$	$\pm 1\%$ of reading +2 $\mu\text{S/cm}$
475 to 4750 $\mu\text{S/cm}$	1 $\mu\text{S/cm}$	$\pm 1\%$ of reading +5 $\mu\text{S/cm}$
4,75 to 47,50 mS/cm	0,01 mS/cm	$\pm 1\%$ of reading +0,05 mS/cm
47,5 to 200,0 mS/cm	0,1 mS/cm	$\pm 2,5\%$ of reading +0,5 mS/cm

Conductivity $K = 0,1$

Range	Resolution	Accuracy
0,00 to 99,99 $\mu\text{S/cm}$	0,01 $\mu\text{S/cm}$	$\pm 1\%$ of reading
100 to 200 $\mu\text{S/cm}$	0,1 $\mu\text{S/cm}$	$\pm 1\%$ of reading

Salinity

Range	Resolution	Accuracy
0,0 to 70,0 ppt	0,1 ppt	$\pm 0,2\%$ Full Scale

Temperature

Range	Resolution	Accuracy
-10,0 to 90,0 $^{\circ}\text{C}$	0,1 $^{\circ}\text{C}$	$\pm 0,2\%$ or $\pm 4\%$ Full Scale whichever is greater

Reference Temp.:	From 15,0 to 25,0 $^{\circ}\text{C}$, default is 25,0 $^{\circ}\text{C}$
Temperature Coefficient:	From 0,00 to 4,00 $^{\circ}\text{C}$, default is 1,91 $^{\circ}\text{C}$
TDS Constant:	From 0,30 to 1,00, default is 0,65
Cell Constant:	4 wire conductivity cell: $K = 0,475$
ATC:	Thermistor, 10K ohms, at 25 $^{\circ}\text{C}$
Power :	9 Volt battery
Size (LxWxD) :	196 x 70 x 37 mm
Weight :	1,36 kg (1 x 9V Battery included)

The CT-480 will be delivered incl. the following standard accessories:
1 x 4-wire conductivity cell 3020P with $k=0,475$
1 x 9 V battery, 1 x operating manual, 1 x carrying case

Code	Description
BOE 5190480	Portable Conductivity/Salinity/TDS/Temperature Meter, Model CT-480 in carrying case with 4-wire Conductivity Cell 3020P with 6 PIN connector, $K=0,475$ (50 μS - 200 mS/cm)

Optional Conductivity Cell:

BOE 5190109	2-wire Conductivity Cell 109P with 6 PIN connector, $K=0,1$ (0,0 - 200,0 $\mu\text{S/cm}$)
-------------	---

BOECO BENCH TOP CONDUCTIVITY/ TDS/SALINITY/TEMP. METER MODEL CT-676

- » Simultaneous displays of conductivity, salinity or TDS with temperature measurements.
- » Convenient one point calibration. Calibration data is stored in memory and is ready for use on power up.
- » Adjustable TDS coefficient, reference temperature and temperature coefficient
- » Uses one conductivity cell for conductivity, salinity and TDS measurement
- » Accepts 4-wire conductivity cells with $k=0,475$ cell constant and 2-wire $K=0,1$ cell constant for improved flexibility and accuracy
- » Low battery indicator
- » IP54 waterproof case

Specification:

Conductivity K = 0,475

Range	Resolution	Accuracy
0,0 to 475 $\mu\text{S/cm}$	0,1 $\mu\text{S/cm}$	$\pm 1\%$ of reading +2 $\mu\text{S/cm}$
475 to 4750 $\mu\text{S/cm}$	1 $\mu\text{S/cm}$	$\pm 1\%$ of reading +5 $\mu\text{S/cm}$
4,75 to 47,50 mS/cm	0,01 mS/cm	$\pm 1\%$ of reading +0,05 mS/cm
47,5 to 200,0 mS/cm	0,1 mS/cm	$\pm 2,5\%$ of reading +0,5 mS/cm

Conductivity K = 0,1

Range	Resolution	Accuracy
0,00 to 99,99 $\mu\text{S/cm}$	0,01 $\mu\text{S/cm}$	$\pm 1\%$ of reading
100 to 200 $\mu\text{S/cm}$	0,1 $\mu\text{S/cm}$	$\pm 1\%$ of reading

Salinity

Range	Resolution	Accuracy
0,0 to 70,0 ppt	0,1 ppt	$\pm 0,2\%$ Full Scale

Temperature

Range	Resolution	Accuracy
-10,0 to 90,0 $^{\circ}\text{C}$	0,1 $^{\circ}\text{C}$	$\pm 0,2\%$ or $\pm 4\%$ Full Scale whichever is greater

Reference Temp.:	From 15,0 to 25,0 $^{\circ}\text{C}$, default is 25,0 $^{\circ}\text{C}$
Temperature Coefficient:	From 0,00 to 4,00 $^{\circ}\text{C}$, default is 1,91 $^{\circ}\text{C}$
TDS Constant:	From 0,30 to 1,00, default is 0,65
Cell Constant	4 wire conductivity cell: $K = 0,475$
ATC	Thermistor, 10K ohms, at 25 $^{\circ}\text{C}$
Power Requirement:	6 x 1,5 Volt AAA batteries or AC adaptor
Dimensions (LxWxH):	150 x 203 x 72 mm
Weight:	2,3 kg (6 x 1,5 V AAA Batteries included)

The CT-676 will be delivered incl. the following standard accessories:
 1 x 4-wire conductivity cell 3020P with $k=0,475$, 6 x 1,5V AAA batteries,
 1 x operating manual, 1 x flexible electrode holder

Code	Description
BOE 5196760	Bench Top Conductivity/Salinity/TDS/Temperature Meter, Model CT-676 with 4-wire Conductivity Cell 3020P with 6 PIN connector, $K=0,475$ (50 μS - 200 mS/cm), with EURO plug
BOE 5196761	Idem, with US plug AC adaptor

Optional Conductivity Cell:

BOE 5190109	2-wire Conductivity Cell 109P with 6 PIN connector, $K=0,1$ (0,0 - 200,0 $\mu\text{S/cm}$)
-------------	---



CT-676